

# MC855

## TECHNICAL BULLETIN

# WOOD RE-BUFF

**WOOD RE-BUFF** is a specially designed buffing solution to buff on Master Woodgard coated timber floor finishes, repair slight scratches, revive/re-polish dull wooden floor and maintain the floor glossiness. Equally effective on Master Epoxeal coated flooring

### USES:

Equally effective on epoxy flooring, laminate, wood and vinyl composition (interior application)

### COVERAGE:

Approximately 5,000 to 20,000 ft<sup>2</sup> (464 to 1,858 m<sup>2</sup>) per gallon (3.785 Lit) depending on the surface conditions and routine maintenance program

### METHOD OF APPLICATION:

1. **Read entire label before using**
2. **TEST A SMALL AREA** according to application instructions to determine the desired results
3. Dust mop floor before buffing
4. Using a trigger spray bottle, spray a light mist onto a manageable area of 10 to 20 ft<sup>2</sup> (1 to 2 m<sup>2</sup>)
5. Buff area immediately for 3 to 5 minutes or until surface is dry with a white or red buffing pad. Low RPM (175 to 300 RPM) floor buffing machine or high speed floor machine (1500 RPM) can be use
6. Repeat the process until the desired result is achieved

### LIMITATIONS:

Keep surfaces clean and dry to reduce possibility of slip-fall accidents



### HANDLING AND STORAGE:

- Avoid contact with skin and eyes
- Close container tightly after each use
- Store in original container only
- Store in cool, dry place with adequate ventilation

### CAUTION:

- **KEEP OUT OF REACH OF CHILDREN**
- **IF INGESTED:** Do not induce vomiting. Seek medical aid at once
- **IF INHALED:** No special requirements under normal use conditions
- **EYE AND SKIN CONTACT:** Flush immediately with plenty of water. If irritation develops, seek medical attention