

MC910

TECHNICAL BULLETIN

STONEGARD

STONEGARD is a natural-look, below-surface sealer designed to resist stains. Allows moisture vapor transmission, repel all water-based fluids effectively from entering into the porous stone, and does not form a coating. Sealer's performances will not be affected by exposure to ultraviolet (UV) rays

USES:

Equally effective for interior and exterior applications on marble, limestone, travertine, granite, terrazzo, grout and cementitious floor

EXPECTED WEAR:

Will vary depending on hardness and texture of surface, type of area, surface wear, frequency and type of maintenance products used, the expected wear is up to 3 years. Extreme weather conditions, harsh cleaning methods and high-alkaline or solvent-based cleaners will affect wear

COVERAGE:

Approximately 500 to 1,000 ft² (46 m² to 93 m²) per coat per gallon (3.785 Lit), depending on type of tile, porosity and texture of surface, temperature, humidity and method of application

MAINTENANCE:

Master Stone Cleaner is recommended for daily maintenance

METHOD OF APPLICATION: SHAKE WELL

1. **Read entire label before using**
2. **TEST A SMALL AREA** with a 24-hour cure time to determine the ease of application and desired results. Test for stain repellence using likely contaminants
3. Wash the top surface of the stone with Master Stone Cleaner (recommended) to remove all dust, dirt and soils before sealer application
4. To give effective protection on porous stone; allow the first coat of sealer to dry in the interior of the stone for at least 2 to 6 hours before applying a second application of sealer
5. Wipe or buff off any excess sealer almost immediately after each sealer application
6. Do not allow excessive sealer to dry on the surface; especially a polished marble and granite surface



7. Ready to surface traffic 20 minutes. Full cure 48 hours upon sealer application
8. Generally one coat is sufficient for polished surface stone and two (2) or more coats of penetrating sealer shall depend on the porosity of the stone. Usually limestone and rough texture stone require two (2) and more applications of sealer

LIMITATIONS:

Do not allow product to come in contact with any non-recommended surface

HANDLING AND STORAGE:

- Close container after each use
- Store in original container only
- Unused, stored product is freeze-thaw stable

CAUTION:

- **KEEP OUT OF REACH OF CHILDREN**
- Eye protection and rubber gloves should be worn during application
- **IF INGESTED:** Do not induce vomiting unless directed by medical personnel. Seek immediate medical attention.
- **IF INHALED:** Move to fresh air
- **EYE CONTACT:** Flush with water for at least 15 minutes. Remove contact lens if worn and seek medical attention
- **SKIN CONTACT:** Immediately flush skin with plenty of water. If irritation persists, seek medical attention

STRIPPER

CLEANER

PROBLEM SOLVER

SEALER/FINISH

POLISHER

MAINTENANCE

