

# MC920

## TECHNICAL BULLETIN

# STONE ENHANCER

**STONE ENHANCER** is an excellent, no-sheen, enhanced-look, penetrating sealer formulated to darken and highlight the character and beauty of unsealed natural stone

### USES:

For all natural stones

### EXPECTED WEAR:

Will vary depending on hardness and texture of surface, type of area, surface wear, frequency and type of maintenance products used, the expected wear is up to 1 - 2 years. Exterior applications may require more frequent re-applications. Weather conditions, harsh cleaning methods and high-alkaline, acidic or solvent-based cleaners will affect wear

### COVERAGE:

Approximately 150 ft<sup>2</sup> to 450 ft<sup>2</sup> (14 m<sup>2</sup> to 42 m<sup>2</sup>) per coat per 946 ml, depending on type of stone, porosity and texture of surface, temperature, humidity and method of application

### TEST A SMALL AREA:

According to application instructions with a 24-hour cure time to determine desired results. Test for stain repellency using likely contaminants. Once enhanced, stone cannot be restored to original color appearance

### METHOD OF APPLICATION:

1. **Read entire label before using**
2. For new installations, sealer can be applied as soon as 48 hours after grouting
3. Surface must be clean, dry, and free of existing sealers and coatings
4. Apply using a sponge, cotton towel
5. If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats. Remove surface residue after each application
6. Ready for surface traffic in 12 hours after final coat. Keep dry for 12 hours. Achieves full cure in 48 hours. Some highly porous surfaces may require an additional coat after full cure

### MAINTENANCE:

Master Stone Cleaner is recommended for ongoing maintenance because many harsh (high-alkaline) cleaners may remove or dull the finish



### LIMITATIONS:

Do not allow sealer to come in contact with any non-recommended surface as product is not completely removable

- Sealers and finishes should not be used before or after use of Master Stone Enhancer
- If Master Stone Enhancer is not WIPED COMPLETELY DRY within 5 minutes, a residue may form

### HANDLING AND STORAGE:

- Close container tightly after each use
- Store in original container only
- Store between temperatures of 40°F – 90°F (4°C – 32°C)

### CAUTION:

- **KEEP OUT OF REACH OF CHILDREN**
- Eye protection and rubber gloves should be worn during application
- **IF INGESTED:** Do not induce vomiting. Seek immediate medical attention
- **IF INHALED:** Move to fresh air. Seek immediate medical attention
- **EYE CONTACT:** Flush with plenty of water for at least 15 minutes immediately. If irritation persists, seek medical attention
- **SKIN CONTACT:** Wash with soap and water. Remove contaminated clothings. If irritation persists, seek medical attention

STRIPPER

CLEANER

PROBLEM SOLVER

**SEALER/FINISH**

POLISHER

MAINTENANCE



Enquiry: sales@mastergroup.asia