

MC933

TECHNICAL BULLETIN

CSS MAX

CSS MAX is a new age nano crystal quartz formulation which enhances and rejuvenates fills up microscopic pores with highly resilient silicate quartz, excellence protector on granite and certain/some agglomerate and tiles, maximize floor luster, excellence shine and durability without losing the slip resistance characteristics of stone and tiles surface.

CSS Max is an evolution single step, user friendly system which also removes light scuff marks; light scratches, and provides maximum durable high quartz gloss finish

COVERAGE:

Approximately 600 to 1,000 ft² (55 m² to 92 m²) per 1 kg

METHOD OF APPLICATION:

1. **Read entire label before using**
2. **TEST A SMALL AREA** according to application instructions to determine desired results
3. Ensure surface is clean and dry
4. Spray or apply CSS Max onto a manageable area of approximately 5 to 10 ft² (0.4 m² to 0.9 m²)
5. Using a synthetic fiber white pad, work area in a side-to-side motion with a 175 to 300 RPM floor machine
6. Add or mix CSS HD for consistency of the CSS Max and be sure to overlap the sections to achieve an even polish
7. Re-apply or continue until the required enhance polish result has been achieved
8. Apply or spray CSS HD as require for higher gloss result as needed depending on surface traffic and consistency of routine maintenance program



HANDLING AND STORAGE:

- Harmful if swallowed
- Avoid contact with eyes
- Close container after each use
- Store in original container only
- Store in dry area

CAUTION:

- **KEEP OUT OF REACH OF CHILDREN**
- **IF INGESTED:** Do not induce vomiting. Drink 1 to 2 glasses of water. Seek medical attention
- **IF INHALED:** Move to fresh air
- **EYE CONTACT:** Flush thoroughly with water. Seek medical attention
- **SKIN CONTACT:** Wash skin with soap and water. Rinse thoroughly. If symptoms persist, seek medical attention