MC936 TECHNICAL BULLETIN

CSS PLASMA

CSS PLASMA is a nano state of the art technology; exactitude mineral formulation reducing the surface oxide crystal, treating and hardening all types of calcareous composition floor surfaces into a highly durable glossy and natural finishes. Removes light scuff marks and scratches; maximize floor luster, excellent shine and durability without losing the slip resistance characteristics

USES:


Excellent on marble, limestone, terrazzo, porcelain, tiles and natural stones

COVERAGE:

Approximately 1,000 ft² (92 m²) per 1 kg

METHOD OF APPLICATION:

- 1. Read entire label before using
- TEST A SMALL AREA according to application instructions to determine desired results
- 3. Ensure surface is clean and dry
- 4. Apply CSS Plasma onto a manageable area of approximately 5 to 10 ft² (0.4 m² to 0.9 m²)
- Using a synthetic fiber white pad, work the area in a side-to-side motion with a 175 to 300 RPM floor machine
- Add Master CSS HD for consistency of the CSS Plasma and be sure to overlap the sections to achieve an even polish
- 7. Re-apply or continue until the required enhance polish result has been achieved
- Apply CSS HD as require for higher gloss result as needed depending on surface traffic and consistency of routine maintenance program



HANDLING AND STORAGE:

- · Harmful if swallowed
- Avoid contact with eyes
- · Close container after each use
- Store in original container only
- Store in dry area

CAUTION:

- KEEP OUT OF REACH OF CHILDREN
- IF INGESTED: Do not induce vomiting. Drink 1 to 2 glasses of water. Seek medical attention
- IF INHALED: Move to fresh air
- **EYE CONTACT:** Flush thoroughly with water. Seek medical attention
- SKIN CONTACT: Wash skin with soap and water.
 Rinse thoroughly. If symptoms persist, seek medical attention



