

MC986

TECHNICAL BULLETIN

DARK CONCEPT (BLACK GRANITE)

DARK CONCEPT (BLACK GRANITE), it rejuvenates the color and improves the appearance of dark and weathered stone. It also effectively restores and enhances to a high gloss, gives an added chemical resistance and preservation properties thus increasing surface traffic and contamination. High density mineral solids reinforced with a base of unique Lithium silicate and Micro Crystal Quartz formulation designed to effectively strengthen and shine on most black color granite stones.

Designed for interior and exterior uses with anti-slippery properties

USES:

Recommended for use on black granite stones

COVERAGE:

Initial treatment approximately:

200 - 300 ft² (18 m² - 28 m²) per 946 ml

Surface Maintenance approximately:

800 - 1000 ft² (74 m² - 93 m²) per 946 ml

METHOD OF APPLICATION: SHAKE WELL

1. **Read entire label before using**
2. **TEST A SMALL AREA**, according to application instructions to determine desired results
3. Ensure surface is clean and dry
4. Spray / apply Dark Concept (Black Granite) onto a manageable area of approximately 5 to 10 ft² (0.5 m² to 1 m²)
5. Using a synthetic fiber white pad, work the area in a side-to-side motion with a 175 to 300 RPM floor machine
6. Be sure to overlap the sections to achieve an even polish
7. Reapply / continue until the required enhance polish result has been achieved
8. Repeat the process if higher gloss require, apply or spray Dark Concept (Black Granite) depending on surface traffic and consistency of routine maintenance program



MAINTENANCE:

- Apply Dark Concept (Black Granite) as require for higher gloss result as needed depending on surface traffic and consistency of routine maintenance program
- Stone Cleaner is recommended for daily maintenance

HANDLING AND STORAGE:

- Close container after each use
- Store in original container only
- Store between 40°F - 90°F (4°C - 32°C)
- Do not swallow and breathe gas/fumes/vapor/spray

CAUTION:

- **KEEP OUT OF REACH OF CHILDREN**
- Eye protection and rubber gloves should be worn during application
- **IF INGESTED:** Drink 1 to 2 glasses of water. Do not induce vomiting unless directed by medical personnel
- **IF INHALED:** Move to fresh air
- **EYE CONTACT:** Flush immediately with large amount of water for at least 15 minutes. Remove contact lenses if worn and seek immediate medical attention
- **SKIN CONTACT:** Flush immediately with large amount of water. Remove contaminated clothings

STRIPPER

CLEANER

PROBLEM SOLVER

SEALER/FINISH

POLISHER

MAINTENANCE